

## GEOMETRY



**NOTE:** The Tempus comes stock with either the Profile Design ASC 52 or 52 A extensions. Tempus builds Force and up have the option to upgrade to the Profile Design ASC Pro Extension for \$600.

FRAME SIZE	S	M	L	XL
[A1] FRAME STACK	466 MM	502 MM	521 MM	539 MM
[A2] PAD STACK (ASC 52/52A Extensions)	582-652 MM	618-688 MM	637-707 MM	655-725 MM
PAD STACK (ASC Pro Extensions) <b>!</b>	562-632 MM	598-668 MM	617-687 MM	635-705 MM
[B1] FRAME REACH	387 MM	417 MM	431 MM	444 MM
[B2] PAD REACH (ASC 52/52A Extensions)	382-487 MM	412-517 MM	426-531 MM	439-544 MM
PAD REACH (ASC Pro Extensions) <b>!</b>	421-473 MM	451-503 MM	465-517 MM	478-530 MM
[C] HEAD TUBE LENGTH	47 MM	86 MM	106 MM	125 MM
[D] CHAINSTAY LENGTH	410 MM	410 MM	410 MM	410 MM
[E] FRONT CENTER	562 MM	603 MM	623 MM	642 MM
[F] WHEELBASE	948 MM	991 MM	1011 MM	1029 MM
[G] BOTTOM BRACKET DROP	76 MM	75 MM	75 MM	75 MM
[H] SEAT TUBE ANGLE	82 Deg	82 Deg	82 Deg	82 Deg
[I] HEAD TUBE ANGLE	72.6 Deg	72.5 Deg	72.5 Deg	72.5 Deg
[J] TOP TUBE LENGTH	452 MM	488 MM	504 MM	520 MM
[K] PHYSICAL SEAT TUBE LENGTH	523 MM	559 MM	579 MM	597 MM
[L] EFFECTIVE SEAT TUBE LENGTH	470 MM	506 MM	526 MM	544 MM
[M] STAND OVER HEIGHT	790 MM	826 MM	845 MM	863 MM
[N] TRAIL	61 MM	61 MM	61 MM	61 MM

**!** ASC Pro Extensions: See Page 13 for a full table of Pad X/Y coordinates.